



FEATURES

- motor grader or wheel loader applications
- quick hitch, quick coupler or pin-on mountings
- left and right angle, v-plow, inverted "v" positions
- quick hitch, quick coupler or pin-on mountings
- full box section moldboard construction
- heavy wall double a-frame tubular construction
- large center pin diameter (3") for long life
- nitrogen accumulators are standard to cushion plow wings
- tapered extended snow shields are standard
- requires two hyd. valves for operation or optional elect/hyd. selector valve

SPECIFICATIONS

| | |
|---------------------------------|------------------------------------------------|
| plow weights* | 3700# to 4400# less mountings |
| plow widths | 12', 14', 16' standard widths |
| plow height | 48" all models |
| moldboard type | smooth rolled, with tapered snow shields |
| moldboard angle to ground plane | 17 degrees |
| moldboard thickness | 1/4" (12', 14' plows), 5/16" (16' plow) |
| moldboard angles | full "v", inverted "v", right or left angle |
| cutting edges | 3/4" x 8" highway punched, alloy |
| hydraulic cylinders and rods | 4" x 2" (12', 14' plows), 5" x 2.5" (16' plow) |
| center hinge pin diameter | 3", greasable |
| optional | mushroom skid shoes |

*weights are for shipping estimates only and will vary due to options and size variations

WWW.RYLIND.COM

RYLIND INDUSTRIES, INC.
6392 WEST MORRAINE PLACE
LITTLETON, COLORADO 80128

GENERAL SALES OFFICE: 303.979.3548 303.979.4730 FAX